

Deck Frame Coating

Rubberized Protective Waterproofing Membrane

**NEW
PRODUCT**

Extend the Life of Your Deck Frame!

FastenMaster Deck Frame Coating extends the life of your deck substructure by creating a protective moisture barrier that deters wood rot and decay on deck joists, beams, ledgers, stair stringers and posts.



Extends Life Of The Deck Frame
Creates a lasting moisture barrier protection



Fast And Clean Application
No mess coverage with less jobsite waste



Dries in as little as 20 minutes **
Sets fast for deck board installation



Coats Hard-To-Reach Places
Use in corners tape cannot reach



Deck Joists



Deck Carrying Beams



Stair Stringers



Can be applied using a standard bristle paint brush or a heavy nap roller.

FastenMaster
Deck Frame Coating



FastenMaster[®] Deck Frame Coating

APPLICATION:

FastenMaster's Deck Frame Coating can be applied using a standard bristle paint brush or a heavy duty, 3/8" nap roller. It is recommended to apply a generous and consistent single layer of coating.

- Apply in temperatures above 40 °F / 4 °C. Freeze/thaw stable when cured.
- Product is in a liquid state, protect from freezing.
If product was frozen, allow 12 hours of thaw time before use.
- Fast dry formula sets in as little as 20 minutes. **
- Full cure in 24 hours @ 70°F/21°C and 50% humidity. **
- Do not apply to dirty/contaminated or wet surfaces.
- Coating remains slightly tacky when cured.


CLEAN UP:

Clean skin or building materials using soap & warm water. Mineral oil or Baby Oil can be used. It is recommended to review the decking manufacturer's warranty before using cleaners.

CAUTION:

Keep out of reach of children & pets. Wear gloves, eye protection and avoid contact with clothing. If in eyes, flush with water for several minutes. Get medical attention if irritation persists. If swallowed call a poison center or doctor for advice. Low VOC waterproofing sealer contains <100g/L VOC.

For use on Deck Joists, Stair Stringers, Deck Carrying Beams, Deck Posts and More!



See How Quick And Easy It Is To Apply



Product Listings

Description	Coverage	SKU
1 gallon bucket	450 LF	FMDFC-1GAL

For a full written warranty, additional engineering data and technical support visit FastenMaster.com.

*Approximate coverage per gallon at 20mil or .5mm dry film thickness

**High temperature and / or high humidity may extend set time.

FM24402 (0924)