



SECTION AT INTERIOR BEARING WALL

ALLOWABLE LOADS BY CONNECTION NUMBER (C#), LOAD TYPE AND SPECIES

| C# | LOAD TYPE | WOOD SPECIES | | |
|----|-----------|--------------|--------|--------|
| | | SPF/HF | D. FIR | S.PINE |
| 1 | UPLIFT | 340 | 560 | 665 |
| 2 | UPLIFT | 210 | 245 | 325 |
| | LATERAL | 340 | 265 | 395 |
| 3 | UPLIFT | 475 | 590 | 595 |
| | LATERAL | 495 | 595 | 650 |
| 4 | UPLIFT | 340 | 560 | 665 |

DESIGNER NOTES

All connections made using 6" FrameFAST Screws (FMFF006) and installed with FramFAST Tool to ensure proper alignment and offset. Where different species being connected, use the value corresponding to the lower density wood.

COMPLIANT TO CODES

IRC, IBC, LABC, LARC, FBC, FRC

SUPPORTING TECHNICAL REPORTS

IAMPO Evaluation Report ER-719
[\(https://www.iapmoes.org/building-products-evaluation-report-program/evaluation-report-directory/\)](https://www.iapmoes.org/building-products-evaluation-report-program/evaluation-report-directory/)
 DRJ Technical Evaluation Reports TER 1503-03, TER 1608-02 and TER 1801-02
 [\(https://www.drjcertification.org/company/fastenmaster\)](https://www.drjcertification.org/company/fastenmaster)

DETAIL #
FM - FF06

REV. DATE
04/13/2023

FastenMaster Framing Details

